

DS-PDD12P-EG2-WB **Detector PIR inalámbrico interior 12 m**



DS-PDD12P-EG2-WB es un detector inalámbrico bidireccional totalmente supervisado que presenta detección de movimiento y microondas. protección contra manipulaciones, batería baja y supervisión. Puede funcionar hasta por 5 años con dos baterías incorporadas y monitorea el área dentro de un radio de 12 m, ignora a los animales y reconoce a los humanos desde el primer paso.

- Óptica 3D que incluye protección contra zonas de fluencia, cobertura total sin ángulos muertos
- Microondas de 24G para evitar la penetración en la pared.
- Compensación de temperatura digital
- Totalmente configurable de forma remota a través de la aplicación
- Método de inscripción múltiple y diseño de instalación sencilla
- Batería fácilmente reemplazable con PCB protegido
- Salto de frecuencia contra interferencias para una transmisión confiable

▪ Specification

Detection Performance	
Detection Method	Passive Infrared,Microwave
Detection Range	12m
Detection Angle	85.9°
Detection Zones	52
Detectable Speed	0.3 ~ 2m/s
Sensitivity	Auto,High,Pet
Pet Immunity	30Kg
White Light Filter	6500lux
Microwave Frequency	24GHz(24.15 ~ 24.25GHz)
Digital Temperature Compensation	Support
Creep Zone Protection	Support
Feature	
Digital Processing	Support
Sealed Optics	Support
Tamper Protection	Front,Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Interface	
Power Switch	Power Up Enrolling
LED Indicator	Green(PIR), Red(Microwave), Blue(Alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1.2Km
Frequency Hopping	Support
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 5 years (standby time)
Power Supply	Battery Powered
Battery Type	CR123A × 2
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	65.5mm × 103mm × 48.5mm
Weight	141g

Mounting Height	1.8 to 2.4m
Mounting Method	Wall
Application Scenario	Indoor
Bracket	Optional Wall & Ceiling Accessory

▪ **Modelo disponible**

DS-PDD12P-EG2-WB

▪ **Accessory**

▪ **Optional**

DS-PDB-IN-Ceiling bracket Internal wall mounted bracket	DS-PDP-IN-CR123A Indoor Detector Battery	DS-PDB-IN-Wall bracket Internal ceiling mounted bracket
		

ventas@rosarioseguridad.com.ar rosarioseguridadok <https://www.facebook.com/groups/591852618012744/>
+54 9 341 6708000 Rosario Seguridad +54 9 341 6591429
+54 9 341 6799822 Rosario Seguridad +54 9 341 4577532

Avenida Presidente Perón 3998 - Rosario - Santa Fe - Argentina

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global

Hikvision
Corporate Channel

hikvisionhq