

Eaton 5E1100IUSB-SEA

Catalog Number: 5E1100IUSB-SEA

Eaton 5E UPS, Tower, 1100VA, 660W, IEC C14 input, Outputs: (6) IEC C13, 230V, AVR, USB



General specifications

Product Name	Catalog Number
Eaton 5E UPS	5E1100IUSB-SEA
Product Length/Depth	Product Height
133 mm	180 mm
Product Width	Product Weight
330 mm	9.22 kg
Compliances	Certifications
CB	IEC/EN 62040-1
CE Marked	IEC/EN 62040-2

Product specifications

Type

UPS

Topology

Line-interactive

Form factor

Tower

Construction type

Free standing model

Color

Black

VA rating

1100 VA

Wattage

660 W

Rack mounting kit

No

Auto shutdown function

Yes

Input connection

C14

Input nominal voltage

230V default (220/230/240V)

Nominal frequency

50/60 Hz

Input frequency range

45-63 Hz

Receptacle

(6) IEC C13

Output waveform

Step wave

Voltage

230V

Output nominal voltage

230V

Feed type

Resources

Brochures

[eaton-5e-ups-user_guides-en-ea](#)

1

Voltage type

AC

Runtime graph

View runtime graph

Battery management

Automatic battery test, deep-discharge protection, cold-start capable

Battery rating

12V / 7Ah

Battery type

Sealed, lead-acid

Extended battery capability

No

Communication

USB port (HID compliant)

Expansion slots

No

Ethernet interface

No

Includes network card

No

Software compatibility

Eaton UPS Companion (enables safe system shutdown, energy usage metering and configuration of UPS settings)

User interface

LED

Type of interface

USB

Potential free switch contact

No

Altitude

2000 m

Noise level

<45 dB at 1 meter

Relative humidity

0-90% non-condensing

Temperature range
0° to 40°C (32° to 104°F)

Battery quantity
2

Input voltage range
170-280 V

Output frequency
50/60 Hz autoselect

Phase (input)
Single-phase

Phase (output)
Single-phase

Runtime at full load
1 min



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2024 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are property of their respective owners.



Eaton.com/socialmedia