

DS-D5AC9C5-8S2 OPS Module



- Intel UHD Graphic, support H.265 and 4K resolution
- Support M.2 nvme system disk quick start
- Support 3 USB 3.0 ports, 3 USB2.0 ports, 1 HDMI port, 1 DP interface, 1 Type-C port
- Support dual channel memory
- Support Wi-Fi IEEE 802.11 a/b/g/n/ac

▪ Specification

Built-in System	
Processor	Intel® Core i5 9400H
CPU Clock Speed	2.5GHz
Platform Architecture	Intel® Coffeelake
PCH	Intel® Z370
Graphics	Intel® UHD Graphics 630
Memory	8G
Storage	256G
NIC	Integrated 10/100/1000M Adaption
Cooling System	Single Brass & Single Fan
Interface	
Network Interface	RJ45×1
Data Transmission Interface	Bluetooth 4.2
Antenna	2
Video Output	HDMI×1, DP×1
Power	
Input Voltage	12V-19V DC
Max. Consumption	60W
Standby Consumption	0.5W
Working Environment	
Storage Temperature	-20°C - 70°C
Storage Humidity	10%-90%
Working Temperature	0°C - 40°C
Working Humidity	10%-90%
General	
Color	Black
Product Dimensions (W × H × D)	180×195×30mm
Net Weight	About 1.24kg

▪ Available Model

DS-D5AC9C5-8S2(海外标配),DS-D5AC9C5-8S2(9400H),DS-D5AC9C5-8S2(9400H)/SHERWOOD



www.rosarioseguridad.com.ar

 ventas@rosarioseguridad.com.ar

  +54 9 341 6708000

  +54 9 341 6799822

 [rosarioseguridadok](https://www.instagram.com/rosarioseguridadok)

 [Rosario Seguridad](https://www.youtube.com/channel/UC...)

 [Rosario Seguridad](https://www.facebook.com/RosarioSeguridad)

Grupo Instaladores

 <https://www.facebook.com/groups/591852618012744/>

  +54 9 341 6591429

  +54 9 341 4577532

Avenida Pellegrini 4820 - Rosario - Santa Fe - Argentina

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq