



C2C (Mini 0)

Simple pero poderoso

Una cámara Wi-Fi HD 720p con base magnética, diseñado para una instalación sencilla y rápida.

Características clave

HD

720p



Soporta MicroSD card slot, hasta 256GB



Soporta 2.4GHz Wi-Fi (IEEE802.11b, 802.11g, 802.11n)



Audio bidireccional



Verdadera cámara día / noche con cambio automatico. Visión nocturna por infrarrojos de hasta 7,5 metros.



Instalación sencilla

El C2C (Mini O) viene con una base magnética y un kit de montaje para colocarlo fácilmente en paredes o techos. Una vez configurado, puede ajustarlo manualmente para cubrir casi cualquier ángulo que necesite.



Video HD 720p con lente gran angular

El C2C (Mini O) ofrece video HD de 720p y una amplia cobertura con una lente gran angular de 111 °, para que pueda vigilar lo que es valioso para usted.



Mantenlos a salvo, día y noche

Cuando está oscuro, el C2C (Mini O) cambia automáticamente al modo de visión nocturna para una cobertura de video HD las 24 horas del día, lo que garantiza una visión nocturna de hasta 7.5 metros.



Alertas instantáneas (se requiere activación manual)

El C2C (Mini O) observa el movimiento.
Tomará una foto y enviará alertas a su teléfono inteligente cuando detecte movimientos



Audio bidireccional

La cámara viene con un micrófono y un altavoz integrados, lo que permite el audio bidireccional a través de la cámara y su teléfono o tableta.



Camara

Image Sensor	1/4" 1MP HD Progressive Scan CMOS
Shutter Speed	Self-adaptive shutter
Lens	2.8mm@F2.5, view angle: 90°, Diagonal View Angle: 111°
Lens Mount	M12
Day & Night	IR-cut filter with auto-switching
DNR	3D DNR
WDR	Digital WDR

Compression

Video Compression	H.264
H.264 Type	Main Profile
Video Bit Rate	HD, Balanced and Smooth. Adaptive bit rate.

Image

Max. Resolution	1280×720
Image Settings	Brightness, contrast, saturation, etc. (configurable via EZVIZ Studio)
BLC	Support

Red

Storage	Supports MicroSD card (max. 256GB)
Smart Alarm	Motion detection
Wi-Fi Pairing Protocol	SmartConfig (Wi-Fi One-Key Configuration)/AP paring EZVIZ Cloud proprietary protocol
Interface Protocol	EZVIZ Cloud proprietary protocol
General Features	Anti-Flicker, Dual-Stream, Heartbeat Messages, Mirror Image, Password Protection, Watermark
Minimum Network Requirements	1Mbps

Wi-Fi

Standard	IEEE802.11b, 802.11g, 802.11n
Frequency Range	2.4 GHz ~ 2.4835 GHz
Channel Bandwidth	Supports 20MHz
Security	64/128-bit WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
Transmission Rate	11b: 11Mbps, 11g: 54Mbps, 11n: 150Mbps

General

Power Supply	DC 5V±10%
Power Consumption	MAX. 3W
IR Range	MAX. 7.5 meters
Product Dimensions	128mm x 58mm x 38mm (0.42ft x 0.19ft x 0.12ft)
Packaging Dimensions	149mm x 91.5mm x 87.5mm
Weight	0.265 lb. (120g)

Package Contents:

- C2C (Mini O) X 1
- 3 Meters USB Cable X 1
- Power Adapter X 1
- Foam Sticker X 2
- Metal Plate (3.5mm Hole Diameter) X 1
- Quick Start Guide X 1

Requirements

- Operating Conditions: -10°C ~ 50°C, Humidity 95% or less (non-condensing)

 **Avenida Presidente Perón 3998 - Rosario - Santa Fe - Argentina**

