HIKVISION

Title:	How to Get IPC MJPEG Stream via HTTP Commands	Version:	v1.0	Date:	16/08/2018
Product:	Cameras			Page:	1 of 3

Preparation

1. The firmware of camera requires V4.1 or above

How to Get IPC MJPEG Stream via HTTP Commands

1. Configure video stream

- a) HTTP commands get stream only be available under Sub stream.
- b) Go to [Configuration]-[Video/Audio]-[Video], set the Stream Type as Sub-stream and Video Encoding as MJPEG. Resolution can be adjusted according to the current condition.

HIKVISION	Live View	Playback P	icture Ap	plication	Configuration
🖵 Local	Video Custom	Video Audio ROI	Display Info. on Str	ream Targe	et Cropping
System	Stream Type	Sub-stream	~		
Network	Video Type	Video Stream	~		
Video/Audio	Resolution	704*576	~]	
Image	Bitrate Type	Variable	~		
Event	Video Quality	Medium	\checkmark		
💾 Storage	Frame Rate	25	~	fps	
CA VCA	Max. Bitrate	1024		Kbps	
Counting	Video Encoding	MJPEG	~		
_ 3	I Frame Interval	50			
	🗎 Sa	ave			

2. Get stream on Firefox or Chrome

HTTP commands is only available on Firefox or Chrome browser.

a) URL:

HTTP without Authentication

http://<IP address of IPC>:<HTTP port>/ISAPI/Streaming/channels/102/httpPreview

HTTP with Authentication

© Hangzhou Hikvision Digital Technology Co.,Ltd. All Rights Reserved.

No.555 Qianmo Road, Binjiang District, Hangzhou 310052, China • Tel: +86-571-8807-5998 • Fax: +1 909-595-0788 E-Mail: <u>support@hikvision.com</u> • <u>www.hikvision.com</u>





Title:	How to Get IPC MJPEG Stream via HTTP Commands	Version:	v1.0	Date:	16/08/2018
Product:	Cameras			Page:	2 of 3

http://<username>:<password>@<IP address of IPC>:<HTTP


port>/ISAPI/Streaming/channels/102/httpPreview

Snapshot using HTTP URL

http://<IP address of IPC>:<HTTP port>/ISAPI/Streaming/channels/1/picture

b) Example:

http://10.9.97.33/ISAPI/Streaming/channels/102/httpPreview http://admin:abcd1234@10.9.97.33/ISAPI/Streaming/channels/102/httpPreview http://10.9.97.33/ISAPI/Streaming/channels/1/picture



Note:

If the HTTP port of the device is still 80 (default), then ":<HTTP port>" is not required; DS-1X23G0 series cameras don't support get MJPEG stream via HTTP commands.





Title:	How to Get IPC MJPEG Stream via HTTP Commands	Version:	v1.0	Date:	16/08/2018
Product:	Cameras			Page:	3 of 3

First Choice for Security Professionals *HIKVISION* Technical Support

