

DS-PDSMK-E-WB

DETECTOR DE HUMO INALAMBRICO 433 MHZ



- Cámara de alta calidad con sensor fotoeléctrico.
- 10 años de duración de la batería

▪ Especificaciones

Detection Performance	
Detection Method	Chamber With Photoelectric Sensor
Feature	
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Self-health Check	Support
Alarm Sound Interlink	Support
Interface	
Power Switch	Power Up Enrolling
LED Indicator	Red (Alarm)
Buzzer	≥ 85dB @ 3 m
Transmission	
Transmission Method	Two-Way RF Wireless
Transmission Frequency	433 MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	1 Km
Enrolling Method	Power up, Remote ID, QR Code
Electrical Characteristics	
Standard Battery Life	10 years for standalone sensor 5 years for RF wireless
Power Supply	Battery Powered
Battery Type	Non Replaceable Energizer L91 x 2 for Sensor Replaceable CR123A x 1 for RF Wireless
Typical Voltage	3 V
General	
Operation Temperature	-10 °C to 50 °C (14 °F to 122 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	5% to 90%
Dimension(WxHxD)	φ120 × 48 mm
Weight	190.5 g
Mounting Method	Ceiling
Application Scenario	Indoor

▪ Modelo disponible

DS-PDSMK-E-WB

www.rosarioseguridad.com.ar

 ventas@rosarioseguridad.com.ar

  +54 9 341 6708000

  +54 9 341 6799822

 [rosarioseguridadok](https://www.instagram.com/rosarioseguridadok)

 [Rosario Seguridad](https://www.youtube.com/RosarioSeguridad)

 [Rosario Seguridad](https://www.facebook.com/RosarioSeguridad)

Grupo Instaladores

 <https://www.facebook.com/groups/591852618012744/>

  +54 9 341 6591429

  +54 9 341 4577532

Avenida Pellegrini 4820 - Presidente Perón 3998 - Rosario - Santa Fe - Argentina

