

DS-PD201PC10-WB
Wireless PIR-Camera Detector



- Detection range: 10m / 90°
- Up to 24KG pet immunity
- Fully remote configurable through App
- Multiple enrollment method and easy installation design
- Easy replaceable battery

▪ Specification

Detection Performance	
Detection Method	Passive Infrared
Detection Range	10m
Detection Angle	90°
Detection Zones	78
Detectable Speed	0.3 ~ 2m/s
Sensitivity	Auto,High,Low
Pet Immunity	24Kg
Feature	
Digital Processing	Support
Sealed Optics	Support
Tamper Protection	Rear
Environment Temperature Indicator	Support
Signal Strength Indicator	Support
Video	
Field Angle	90°(H), 70°(V)
Image Type	JPEG
Resolusion	320*240,160*120
Interface	
Power Switch	Power Up / Enrolling
LED Indicator	Blue(Alarm)
Transmission	
Transmission Technology	Tri-X Wireless
Transmission Frequency	433MHz
Transmission Security	AES-128 Encryption
Transmission Range(Free Space)	800m
Enrolling Method	Power up,Remote ID,QR Code
Electrical Characteristics	
Standard Battery Life	Up to 2 years (standby time)
Power Supply	Battery Powered
Battery Type	AA Alkaline Battery × 4
Typical Voltage	3V
General	
Operation Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Storage Temperature	-20 °C to 60 °C (-4 °F to 140 °F)
Operation Humidity	10% to 90%
Dimension(WxHxD)	65.6mm × 104mm × 50.7mm
Weight	120g
Mounting Height	2.0m - 2.4m
Mounting Method	Wall
Application Scenario	Indoor
Bracket	Optional Wall Accessory

▪ **Available Model**

DS-PD201PC10-WB

▪ **Accessory**

▪ **Optional**

DS-PDB-IN- Wallbracket Internal wall mounted bracket	DS-PDB-IN-UBKT1 Internal universal bracket1
	

See Far, Go Further



www.hikvision.com
support@hikvision.com



© Hangzhou Hikvision Digital Technology Co., Ltd. Unless otherwise agreed, Hikvision makes no warranties, express or implied. We reserve the right to introduce modifications without notice.

HIKVISION®