



TP-Link VIGI C340I 2.8MM cámara de vigilancia Bala (forma) Cámara de seguridad IP Exterior 2560 x 1440 Pixeles Techo/pared/Tubo



Marca : TP-Link

Familia de productos: VIGI

Código del producto: VIGI
C340I 2.8MM

Nombre del producto : VIGI
C340I 2.8MM

Cámara IP VIGI tipo bullet con IR para exteriores de 4MP, 2560 × 1440, CMOS de barrido progresivo de 1/3", 2.8 mm, F 2.2, IR Cut Filter, IP67

TP-Link VIGI C340I 2.8MM. Tipo: Cámara de seguridad IP, Colocación compatible: Exterior, Tecnología de conectividad: Alámbrico. Tipo de montaje: Techo/pared/Tubo, Color del producto: Negro, Blanco, Factor de forma: Bala (forma). Iluminación mínima: 0.01 Lux, Ángulo de visión del objetivo, horizontal: 88.8°, Ángulo de visión del objetivo, vertical: 48.9°. Tipo de sensor: CMOS, Tamaño del sensor óptico: 25.4 / 3 mm (1 / 3"). Distancia de detección: 60 m, Distancia de observación: 25 m, Distancia de reconocimiento: 12 m

Performance		Video	
Type *	IP security camera	Region of Interest (ROI) encoding	✓
Placement supported *	Outdoor	Smart IR	✓
Connectivity technology *	Wired	3D positioning	✓
Wide Dynamic Range (WDR)	✓	Audio	
Day/night mode	✓	Signal-to-Noise Ratio (SNR)	52 dB
Infrared (IR) cut-off filter	✓	Network	
Design		Ethernet LAN *	✓
Form factor *	Bullet	Networking standards	IEEE 802.3af, IEEE 802.3at
Mounting type *	Ceiling/Wall/Pole	Supported network protocols	TCP/IP, UDP, ICMP, HTTP, HTTPS, DHCP, DNS, RTSP, NTP, UPnP UDP, SSL/TLS
Product colour *	Black, White	Wi-Fi *	✗
Housing material	Plastic	Bluetooth *	✗
International Protection (IP) code	IP67	Number of simultaneous live view channels	3 channels
Camera		Ports & interfaces	
Minimum illumination	0.01 lx	Ethernet LAN (RJ-45) ports	1
Lens viewing angle, horizontal	88.8°	DC-in jack	✓
Lens viewing angle, vertical	48.9°	Security	
Lens viewing angle, diagonal	106.5°	Password protection	✓
Tilt angle range	-90 - 90°	Video motion detection	✓
Pan range	-90 - 90°	IP address filtering	✓
Camera shutter speed	1/3 - 1/10000 s	HTTPS encryption	✓
Number of Privacy masking areas	4	Intelligent Video Surveillance (IVS) system features	Crossing line, Region entrance detection, Region exiting detection, Vehicle detection
Image sensor		Mirror	✓
Optical sensor size	25.4 / 3 mm (1 / 3")	Password reset via email	✓
Progressive scan	✓	Human and vehicle targets classification	✓
Sensor type *	CMOS	Digest authentication	✓
Lens system		Network access storage (NAS)	✓
Number of lenses *	1	Management features	
Detect distance	60 m	Web browser	✓
Observe distance	25 m		
Recognize distance	12 m		
Maximum aperture number	2.2		
Identify distance	6 m		
Fixed focal length	2.8 mm		
Night vision			
Night vision *	✓		
Night vision distance	30 m		

Night vision		Management features	
LED type	IR	Behavior analysis	Intrusion detection, Line crossing detection, Object removal detection, Region entrance detection, Region exiting detection
Number of illumination LEDs	2		
Infra-red wavelength	850 nm		
Video		Power	
Maximum resolution *	2560 x 1440 pixels	Power source type *	DC, PoE
Total megapixels *	4 MP	Power consumption (typical)	1.32 W
Video compression formats	H.264, H.264+, H.265, H.265+	Power consumption (max)	5 W
Supported graphics resolutions	320 x 240, 352 x 288, 640 x 480 (VGA), 1280 x 720 (HD 720), 1920 x 1080 (HD 1080), 2048 x 1280, 2304 x 1296, 2560 x 1440	DC output voltage	12
		Operational conditions	
Supported video modes	240p, 480p, 720p, 1080p, 1280p, 1440p	Operating temperature (T-T)	-30 - 60 °C
Frame rate	30 fps	Storage temperature (T-T)	-40 - 60 °C
Video streaming	✓	Operating relative humidity (H-H)	0 - 95%
Image quality adjustment	Brightness, Contrast, Mirror, Saturation, Sharpness	Storage relative humidity (H-H)	0 - 95%
Privacy masking	✓	Weight & dimensions	
Bit rate control	Constant Bit Rate (CBR)/Variable Bit Rate (VBR)	Width	73 mm
Bit rate	256 Kbps - 4 Mbps	Height	71 mm
Back Light Compensation (BLC)	✓	Length	174 mm
Highlight Compensation (HLC)	✓	Weight	200 g
Digital Wide Dynamic Range (DWDR)	✓	Packaging data	
		Package width	128 mm
		Package depth	218 mm
		Package height	103 mm
		Package weight	360 g
		Package type	Box
		Sustainability	
		Sustainability compliance	✓
		Compliance certificates	BSMI, CE, EAC, Federal Communications Commission (FCC), UKCA
		Packaging content	
		Number of cameras *	1
		Mounting kit	✓
		Manual	✓



4897098688991

www.rosarioseguridad.com.ar

 ventas@rosarioseguridad.com.ar

 +54 9 341 6708000

 +54 9 341 6799822

 [rosarioseguridadok](https://www.instagram.com/rosarioseguridadok)

 Rosario Seguridad

 Rosario Seguridad

Grupo Instaladores

 <https://www.facebook.com/groups/591852618012744/>

 +54 9 341 6591429

 +54 9 341 4577532

Avenida Pellegrini 4820 - Presidente Perón 3998 - Rosario - Santa Fe - Argentina



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.

Publication date: 11-APR-2025. Prints or copies of Information are only valid on the printed Publication date

